PIF 01474

LOW VOC

PROCLEAN

STAIN REMOVER & DEGREASER

87 g/L

UNDER THE SCAQMD 100 G/L LIMIT

pH 10 | Use as supplied | 87 g/L VOC | Cherry odor

Textile Printing | Manual

DESCRIPTION

ProClean is a stain remover and degreaser that removes remaining stains from screens during the reclaiming process. It degreases the screen in the same step and helps prevent ghost images. Low in VOC with a cherry odor, ProClean is a must-have for textile printers.

ADVANTAGES

Fast Haze Removal
Lifts remaining stains during reclaim

Two Steps in One
Removes stains and degreases; no extra degreaser

Low Cost per Screen
$0.16 per screen at 0.5 fl oz (drum MSRP)

Low VOC
87 g/L, under the SCAQMD 100 g/L limit

DIRECTIONS

- Apply as supplied by spray, towel or brush to the print side of the screen. Scrubbing both sides usually gives better results.
- Rinse immediately with high-pressure water, working side to side and bottom to top.
- Finish with a flood rinse over the entire frame and mesh to remove any trace of chemical.
- Let the screen dry completely before reuse.
- Use in a well-ventilated area away from heat and flame; wear gloves and eye protection.

55 gal drum 01474-D5505 | **5 gal pail** 01474-P5010 | **1 gal · 4 × 1 gal** B1201 · C4201 | **12 × 1 qt** 01474-C3002

COST PER SCREEN

FL OZ PER SCREEN	SCREENS PER GAL	SCREENS PER DRUM	COST PER SCREEN
0.5 fl oz (reference)	256	14,080	$0.16
1 fl oz	128	7,040	$0.32

Reference use: 0.5 fl oz per screen, about 15 trigger sprays at 1 ml per spray, for $0.16 per screen. Cost = fl oz used × $0.32 per fl oz ($40.52/gal, 55 gal drum MSRP, effective July 3, 2026). Actual use varies with screen size and ink load; your distributor price may differ.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
01474-D5505	55 gal drum	Not regulated
01474-P5010	5 gal pail	Not regulated
01474-C4201	4 × 1 gal	Not regulated
01474-B1201	1 gal bottle	Not regulated
01474-C3002	12 × 1 qt	Not regulated

PIF 01474 · TDS rev02 · Issued October 19, 2026 · Supersedes rev01

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

PROCLEAN

WHERE IT FITS IN THE RECLAIM PROCESS

1 INK REMOVAL
Bio-1 · Bio-4 · Bio-11

› 2 EMULSION REMOVAL
ER-160 · ER-190 · ER-1-2-5

› 3 STAIN REMOVAL (HAZE)
ProClean (this product)

› 4 DEGREASE
ProClean (this product)

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Straw-colored, clear liquid	**Flash point**	165°F (74°C)
Odor	Ester and cherry	**VOC**	8% by weight (87 g/L)
pH	10	**Evaporation rate**	<1 (n-butyl acetate = 1)
Specific gravity	1.080	**Solubility in water**	Negligible
Weight, per U.S. gallon	9.0 lb	**Stability**	Stable

SAFETY & HANDLING

HAZARDS (GHS)

- Combustible liquid (H227)
- Harmful if swallowed (H302)
- May be fatal if swallowed and enters airways (H304)
- Causes skin irritation (H315)
- Causes serious eye irritation (H319)
- May cause drowsiness or dizziness (H336)

FIRST AID

- **If swallowed:** Immediately call a poison center or doctor. Do NOT induce vomiting (aspiration hazard). Rinse mouth.
- **If on skin or hair:** Wash well with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if irritation persists.
- **If inhaled:** Move to fresh air and keep at rest. Call a poison center or doctor if you feel unwell.
- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses. Get medical attention if irritation persists.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles, and a face shield.
- **Hands & body:** Chemical-resistant (impervious) gloves; normal work clothing.
- **Breathing:** Use only in a well-ventilated area. NIOSH-approved respirator if the PEL is exceeded.

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame and sunlight; keep cool. Keep tightly closed, locked up, away from oxidizers, acids, bases and reducers.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of per federal, state and local regulations.

Safety information summarized from the ProClean Safety Data Sheet. The SDS governs; see it for full precautions.

REGISTRATIONS & COMPLIANCE

GHS signal word	WARNING
VOC	8% by weight (87 g/L)
California SCAQMD Rule 1171	Compliant
California Prop 65	Contains no listed chemicals
DOT, ground	Combustible liquid: not regulated in containers of 119 gal or less (49 CFR 173.150(f)(2)); NA1993, PG III at 120 gal or more.
Air and vessel	Air: 60 L max per package passenger, 220 L cargo aircraft. Not a marine pollutant.

ORDERING & SUPPORT

- **Orders:** 800-752-6627 · sales@kor-chem.com · shop.kor-chem.com
- **SDS:** scan the code below or visit kor-chem.com/sds
- **Find a distributor:** kor-chem.com/distributor-locator
- **Technical service:** our screen printing team can help fit ProClean into your textile reclaim line.
- **Next step:** ProClean removes stains and degreases, so the dry screen is ready to recoat with emulsion; for new mesh, degrease with DG-520.
- **Equipment:** Kor-Chem also supplies dip tanks, spray guns, scrub pads and InPro TigerClean automatic screen reclaiming systems.
- **Made in Atlanta:** manufactured by Kor-Chem, Inc., Atlanta, Georgia.

PIF 01474 · TDS rev02 · Issued October 19, 2026 · Supersedes rev01

Read the product label and Safety Data Sheet before use. Orders: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM

ATLANTA, GEORGIA 30336
MAIN OFFICE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.