PIF 02513

PRESSURE MAX

HEAVY-DUTY PRESSURE WASH DETERGENT

DILUTES UP TO

1:128

WITH WATER

pH 12.5–13.5 | 1:128–1:32 | 0% VOC

Hard surfaces | Vehicle

DESCRIPTION

Pressure Max is a heavy-duty pressure wash detergent built on biodegradable surfactants and chelants. It removes grease, grime, oil, AC fluid and mold and mildew staining with little or no agitation and leaves surfaces free of residue. Use it at high or low pressure, in hot or cold water. Non-butyl and non-flammable.

ADVANTAGES

Residue-Free Cleaning
Cleans many surfaces and leaves no residue

Any Pressure, Any Temp
High or low pressure, hot or cold water

Non-Butyl, Non-Flammable
No butyl solvents; 0% VOC

Biodegradable
Biodegradable surfactants; non-phosphate

MIXING & USE DIRECTIONS

1. Dilute in hot or cold water to the ratio for the job (see Dilution Guide) and apply with low- or high-pressure equipment.
2. **Roofs & buildings:** Apply with conventional or airless spray equipment at about 200–250 sq ft per gallon. Allow the solution to remain on the surface at least 15–20 minutes, then rinse with pressure washing equipment capable of 2,000 PSI.
3. Always rinse thoroughly with clean water so no cleaner residue remains.

DILUTION GUIDE

USE	RATIO	CONCENTRATE PER GAL OF WATER
Routine maintenance	1:128	1.0 fl oz
Light duty	1:85	1.5 fl oz
Medium duty	1:64	2.0 fl oz
Heavy duty	1:32	4.0 fl oz

Ratios from the dilution chart. Concentrate per gallon of water = 128 ÷ ratio.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
02513-D5505	55 gal	Not regulated
02513-P5004	5 gal	Not regulated
02513-C4001	4 × 1 gal	Not regulated

PIF 02513 · TDS rev05 · Issued October 2026 · Supersedes rev04

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

PRESSURE MAX

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Colorless, clear liquid	**Flashpoint**	Not flammable
Odor	Characteristic	**Solubility**	Complete in water
pH	12.5–13.5	**VOC**	0%
Specific Gravity	1.045	**Foam**	Very low
Weight, per U.S. gallon	8.7 lbs	**Max. Dilution Ratio**	1:128 with water
Viscosity	Thin		

SAFETY & HANDLING

HAZARDS (GHS)

WARNING

- Causes serious eye irritation (H319)
- Causes skin irritation (H315)
- Mists or sprays may irritate the respiratory tract
- Swallowing may irritate the digestive tract

FIRST AID

- **If in eyes:** Flush with water for at least 15 minutes, holding eyelids open. Remove contact lenses and keep rinsing. Get medical attention if irritation persists.
- **If on skin:** Wash with soap and water. Launder contaminated clothing before reuse.
- **If swallowed:** Do NOT induce vomiting. Rinse mouth. Call a physician immediately.
- **If inhaled:** If symptoms develop, move to fresh air.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles
- **Hands & body:** Chemical-resistant (impervious) gloves; normal materials-handling clothing
- **Breathing:** NIOSH-approved protection if mists or sprays are generated and cause irritation

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame or sunlight. Keep container closed when not in use. Protect from physical damage.
- Store away from oxidizing agents, acids, aluminum, zinc, tin, copper and their alloys.
- **Disposal:** Do not dump into sewers, on the ground or into any waterways. Dispose of contents and container per federal, state and local regulations. Emptied containers retain residue; follow label warnings and do not cut, drill, grind or weld on or near them.

Safety information summarized from the Pressure Max Safety Data Sheet. The SDS governs; see it for full precautions.

RECOMMENDED APPLICATIONS

- Pressure Washing
- Vehicle Frames
- Tires & Wheels
- Engines
- Shop Floors
- Metal Parts
- Rubber & Plastic
- Concrete
- Buildings
- Roof Cleaning
- Smooth & Granule Roofs

REGISTRATIONS & COMPLIANCE

VOC	0%
GHS signal word	WARNING
DOT, all pack sizes	Not regulated

ORDERING & SUPPORT

- Order: 800-752-6627 · sales@kor-chem.com
- Phone: 404-344-9580
- SDS: scan the code below or visit kor-chem.com/sds
- Find a distributor: kor-chem.com/distributor-locator

PIF 02513 · TDS rev05 · Issued October 2026 · Supersedes rev04

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS
kor-chem.com/sds

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.