EASY CLEAN

DETERGENT DEGREASER

WORKS IN

5–10 min

ON WARM SURFACES

pH 13–14 | Use undiluted | Hot or cold surfaces

Kitchen

DESCRIPTION

Easy Clean is a professional-strength oven and grill cleaner and degreaser for the toughest jobs in commercial kitchens. Fast-acting detergents and strong alkaline builders loosen grease, oil, carbon, smoke film and baked-on residue on contact, so soils wipe away easily. Easy Clean takes the scrubbing out of grill cleaning and saves time.

ADVANTAGES

Removes Carbon & Grease
Loosens carbon, grease and baked-on residue

Hot or Cold Surfaces
Works on hot or cold ovens and grill tops

Fast Acting
Begins to work on contact; wipes away easily

Commercial Strength
Commercial strength formula that is easy to use

DIRECTIONS

1. For best results, preheat the oven to between 180 and 200°F.
2. Spray or brush Easy Clean undiluted onto the surface and allow to work for 5 to 10 minutes. On cold surfaces, allow to soak for 10 to 15 minutes.
3. Wipe clean with a sponge or damp cloth. Reapply to stubborn areas if necessary.
4. Use a scouring pad or steel wool pad on heavy deposits.

AVAILABLE PACK SIZES

ITEM NO.	PACK SIZE	DOT
03048-D5503	55 gal	UN1760, 8, PG II
03048-C4502	4 × 1 gal	UN1760, 8, PG II
03048-C3001	12 × 1 qt	Limited Quantity

PIF 03048 · TDS rev05 · Issued October 2026 · Supersedes rev04

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS

kor-chem.com/sds

KOR-CHEM

ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

EASY CLEAN

TYPICAL PRODUCT CHARACTERISTICS

Appearance	Yellow, clear liquid	**Flashpoint**	Not flammable
Scent	Slight ammonia	**Solubility**	Complete in water
pH	13–14	**Foam**	Low
Specific Gravity	1.100	**Emulsification**	Very good
Weight, per U.S. gallon	9.2 lbs	**Rinsability**	Very good

SAFETY & HANDLING

HAZARDS (GHS)

DANGER

- Causes severe skin burns and eye damage (H314)
- Causes serious eye damage (H318)
- May be corrosive to metals (H290)
- Harmful if swallowed (H302)
- May be harmful if swallowed and enters airways (H305)
- Harmful to aquatic life (H402)

FIRST AID

- **If in eyes:** Flush immediately with water for at least 15 minutes, holding eyelids open. Remove contact lenses and keep rinsing. Get medical attention immediately.
- **If on skin:** Remove contaminated clothing. Wash with soap and water, then flush with water for 15 minutes. Get medical attention if irritation persists.
- **If swallowed:** Do NOT induce vomiting. Rinse mouth. Get emergency medical help immediately.
- **If inhaled:** Move to fresh air and keep at rest. Get medical attention; lung symptoms can be delayed up to 48 hours.

PROTECTIVE EQUIPMENT

- **Eyes:** Safety glasses with side shields or splash-proof goggles and face shield
- **Hands & body:** Chemical-resistant gloves; normal materials-handling clothing and apron
- **Breathing:** NIOSH-approved protection if PEL is exceeded or mists/sprays are generated

STORAGE & DISPOSAL

- **Shelf life:** 1 year minimum at 75°F in the original closed container.
- Keep from freezing.
- **Lot number:** bottom right corner of every label, a Julian date followed by the item number.
- Keep away from heat, flame or sunlight. Keep container tightly closed; keep only in original container. Store locked up.
- Store away from strong acids, halogenated compounds and prolonged contact with metals or alloys.
- **Disposal:** Do not dump into sewers, on the ground or into waterways. Dispose of contents and container per federal, state and local regulations. Emptied containers retain residue; follow label warnings. Waste may be RCRA hazardous waste D002 (corrosive).

Safety information summarized from the Easy Clean Safety Data Sheet. The SDS governs; see it for full precautions.

RECOMMENDED APPLICATIONS

- Ovens
- Grills
- Fryers
- Frying Pans
- Stove Burners

PIF 03048 · TDS rev05 · Issued October 2026 · Supersedes rev04

Read the product label and Safety Data Sheet before use. Order: 800-752-6627 · sales@kor-chem.com

SCAN FOR SDS

kor-chem.com/sds

KOR-CHEM

ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.

EASY CLEAN

REGISTRATIONS & COMPLIANCE

GHS signal word	DANGER
DOT, 55 gal & 4 × 1 gal	UN1760, Corrosive liquid, n.o.s. (sodium hydroxide), Class 8, PG II. Gallons do not qualify for Limited Quantity (PG II limit is 1 L per inner container).
DOT, 12 × 1 qt	Limited Quantity

ORDERING & SUPPORT

- Order: 800-752-6627 · sales@kor-chem.com
- Phone: 404-344-9580
- SDS: scan the code below or visit kor-chem.com/sds
- Find a distributor: kor-chem.com/distributor-locator

KOR-CHEM
ATLANTA, GEORGIA 30336
PHONE: 404-344-9580
E-MAIL: sales@kor-chem.com
WEB: www.kor-chem.com

Information contained herein, is to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use are beyond our control, Kor-Chem Inc. disclaims any liability in connection with the use of our products and information contained herein. No person is authorized to make any statement or recommendation not contained herein, and any such statement or recommendation made shall not bind Kor-Chem Inc. Nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use, and no license implied or in fact is granted herein under the claims of any patent.